




TANDBERG Codian MCU 4500 Series

The TANDBERG Codian MCU 4500 Series is the industry's leading full high-definition multimedia conferencing bridge. It delivers superior video and voice with an easy-to-use, versatile management interface. Compatible with all major vendors' endpoints, each model maintains its capacity and performance in every configuration, delivering the best experience for each participant, every time.



DESIGN FEATURES

- Standards-based and compatible with all major vendors' endpoints
- Easy-to-use, versatile management interface
- Up to 40 video plus 40 voice ports
- Over 50 custom layouts
- Comprehensive wideband audio support
- Support for both SIP and H.323 endpoints
- PacketSafe™ technology minimizes effects of network packet loss
- Compact size: 2U tall and 19" rack mountable

APPLICATION FEATURES

- TANDBERG Codian ConferenceMe™ for multipoint desktop video
- Enables transition from SD to HD using TANDBERG Codian ClearVision™
- Integrated with TANDBERG Management Suite (TMS)
- Offers full interoperability with ISDN networks using stand-alone TANDBERG Codian or third party ISDN gateways
- Compatible with Microsoft Office Communication Server
- Fully integrated, with built-in gatekeeper and streaming server
- Multiway™

PERFORMANCE FEATURES

- High Definition Continuous Presence on every port
- TANDBERG Codian Universal Port™ technology ensures each participant receives the best possible experience
- Constant high capacity
- Bandwidth per site up to 4 Mbps
- Video resolutions up to 1080p 30fps

GET THE MOST FROM YOUR INVESTMENT. WITH PROFESSIONAL SERVICES, TANDBERG EXPERTS SUPPORT TANDBERG CODIAN MCU 4500 SERIES DEPLOYMENT AND TRAINING. VISIT WWW.TANDBERG.COM

TANDBERG

TANDBERG is now part of Cisco.



MODEL	VIDEO PARTICIPANTS	WITH 1080P CAPACITY UPGRADE OPTION	ADDITIONAL VOICE PARTICIPANTS	VIDEO STREAMING UNICAST/MULTICAST
MCU 4505	12 x 720p 6 x 1080p	12 x 1080p	12	24/unlimited
MCU 4510	20 x 720p 10 x 1080p	20 x 1080p	20	40/unlimited
MCU 4515	30 x 720p 15 x 1080p	30 x 1080p	30	60/unlimited
MCU 4520	40 x 720p 20 x 1080p	40 x 1080p	40	80/unlimited

VFO-4500	Video Firewall Option — enables second Ethernet connection to additional networks (e.g. Internet)
WCO-4505/WCO-4510/WCO-4515/WCO-4520	Web Conferencing Option — includes TANDBERG Codian ConferenceMe™ for multipoint desktop video; alternatively provides content streaming, annotation and chat capabilities
MHD-4505/MHD-4510/MHD-4515/MHD-4520	1080p Capacity Upgrade Option — enables maximum HD port count at 1080p

*Maximum number of unicast streams is dependent on network topology. When using the WCO feature, the maximum number of unicast streams supported by the 4515 and 4520 is 50.

HIGH-DEFINITION PERFORMANCE

Up to 1080p 30 fps H.264 4 Mbps continuous presence
Comprehensive HD audio
Dual video H.239

VIDEO STANDARDS

H.261, H.263, H.263+, H.263++, H.264

VIDEO RESOLUTION

From QCIF up to 1080p (1920 x 1080) including interlaced iCIF and iSIF
4:3 and 16:9 aspect ratios

FRAME RATES

30 frames or 60 fields per second

AUDIO STANDARDS

G.711, G.722, G.722.1, G.723.1, G.728, G.729, MPEG-4 AAC-LC, MPEG-4 AAC-LD, Polycom® Siren14/G.722.1 Annex C

PROTOCOLS

H.323, SIP, H.235 (AES), SRTP, TLS, H.239 (dual video), VNC™, BFCP, H.243 (chair control), FTP, RTP, RTSP, HTTP, HTTPS, DHCP, SNMP, NTP, NTLM (authentication)

BANDWIDTH

Up to 4 Mbps with both H.263 and H.264, for each site in all conference modes including advanced continuous presence

UNIVERSAL TRANSCODING AND TRANSTRATING

Combine HD and SD within the same conference
Automatic audio/video transcoding and transrating on all calls
Any bandwidth, any resolution, any video or audio codec can be used on any video call within the same conference
Each participant has their own personal encode

STREAMING VIDEO

Built-in streaming server
View using Windows Media Player™, RealPlayer™ or QuickTime™
Streaming of slides (H.239 and VNC™)
Text chat
Unicast and multicast
UDP, TCP or HTTP
Independent choice of bandwidth and codec

LOCALIZATION AND CUSTOMIZATION

Custom IVR/auto attendant audio prompts and graphics
Uploadable multi-language support
Unicode conference and site names

MCU FEATURES

Dial in or dial out via Web server
Standalone or using gatekeeper
Configurable audio and video auto attendant
Advanced continuous presence as standard on all ports
Automatic selection of best layout
Individual layout selection using remote control or Web pages
Over 50 custom layouts
Widescreen (16:9) support
Active speaker selection using remote control or voice activated
Floor assignment through Web page or management application
Far-end camera control tunneling using remote control or Web
Text identification of sites
On-screen text messaging to individual or all sites
Built-in conference scheduling and reservation
On-demand and ad hoc conferences
Dual video using H.239
Presentation mode: add slides from PC using VNC™
Automatic lecture mode
Preview of conference and individual camera on Web pages
Web Conferencing Option — those without endpoints can still interact
Uploadable bitmaps for voice participants
Video association for IP and traditional PBXs
Automatic connection to audio conferences
Multiway™ — enables TANDBERG video endpoints to initiate ad hoc multiparty calls

TANDBERG CODIAN CONFERENCE™

Content Sharing
Multiple layouts
Firewall friendly
Independent transcode per participant
Up to 12 simultaneous connections
Client computer requirements:
Refer to the list of verified PCs and Webcams under the support section of the TANDBERG website

AUDIO FEATURES

Wideband audio mixing
Built-in and uploadable auto attendant voice prompts
Automatic gain control, adjustable gain, power indication, individual audio mute using web pages

BUILT-IN WEB SERVER

Complete configuration, control and monitoring of the system and conferences

BUILT-IN GATEKEEPER

Resolution of E.164 numbers
Registration of conferences, endpoints and gateways
Up to 25 devices can register

SYSTEM MANAGEMENT

XML management API
Management via embedded web server
RS-232 for local control and diagnostics
Syslog for diagnostics
Configurable event logs and full H.323 and SIP decoding
Configuration backup to network
Secure upgrades through Ethernet or CompactFlash
Call Detail Records
SNMP

QUALITY OF SERVICE

Configurable DSCP or TOS/IP precedence

NETWORK RESILIENCE

Codian Packet Safe™ technology provides intelligent downspeeding, packet pacing and packet loss concealment to ensure optimum video and audio quality
Dynamic jitter buffering
Alternate gatekeepers

SECURITY FEATURES

Seven levels of access rights and privileges for users
Strong password policy
Pin-protected conferences
Conference locking
Secure non-PC hardware and operating system
AES encryption, 128 bit key, H.235
SIP encryption
TLS certificate verification
VFO — second Ethernet port
Audit log

INTERFACES

RJ45 Ethernet, 10/100/1000 Mbps full/half duplex, manual or auto sensing
RJ45 serial port
CompactFlash socket
39 status LEDs

ENVIRONMENTAL DATA

Operating temperature 0°C to 35°C ambient
Relative humidity below 95% (non-condensing)

PHYSICAL DIMENSIONS

Height 3.43'; 87 mm (2U)
Width 17.4'; 442 mm
Depth 19.25'; 489 mm
Weight 33 lbs, 15 kg
19" rack mountable (kit supplied) or standalone
Power 100-240 VAC, 50/60Hz
600W maximum power consumption

APPROVALS AND COMPLIANCE


European safety: EN 60950-1:2001
USA safety: UL 60950-1 First Edition
Canada safety: CSA 60950-1-03
CB Scheme certificate, CE Marked
EMC:
EN55022 class A,
EN61000-3-2, EN61000-3-3,
EN55024: EN61000-4-2, -3, -4, -5, -6, -11,
FCC Part 15 class A,
VCCI class A,
AS/NZS 3548 (C-Tick),
CCC Approved: GB4943-2001, GB9254-1998,
YD/T993-1998
NAL Certificate (China)
RoHS compliant

All specifications subject to change without notice, system specifics may vary.

All images in these materials are for representational purposes only, actual products may differ.

TANDBERG and Codian are registered trademarks or trademarks of TANDBERG in the U.S. and other countries.

All other trademarks are property of their respective owners.



TANDBERG

Codian MCU 4500 Series

TANDBERG WORLD HEADQUARTERS

Philip Pedersens vei 20
1366 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 126 126
tandberg@tandberg.com

1212 Avenue of the Americas,
24th Floor
New York, NY USA 10036
Tel: +1 212 692 6500
Fax: +1 212 692 6501
Video: +1 212 692 6535
tandberg@tandberg.com

May 2010